

FIRE PROTECTION

CLASSES OF FIRE:

Fires are classified according to the material that is burning. Fire extinguishers are rated by the area each will cover for a particular class of fire. The higher the number, the bigger the fire area you can fight.

Note: Maintenance and recharging of all fire extinguishers should be performed by a qualified service company.



CLASS A fires are the most common. They involve ordinary combustibles such as wood, paper, cloth, rubber, a number of plastics, and other ordinary materials.



CLASS B fires are caused by gasoline, grease, oil, paint and other flammable liquids. Commonly strikes in warehouses and manufacturing plants.



CLASS C for live electrical equipment. Often occurs in computers, monitors, wiring and appliances.

STEEL DRY CHEMICAL ABC FIRE EXTINGUISHERS

- Steel cylinder complete with cylinder skirt
- Industrial-strength cylinder has high corrosion and impact-resistant polyester powder paint finish
- Waterproof stainless steel gauge
- Anodised aluminum valve
- Strong polyester powder-coated steel handles
- Completely rechargeable
- Full hand grip for ease of operation
- ULC listed

SC951
Wall Hooks



Model No.	Mfg. No.	Cap. lbs.	Rating	Range Feet	Discharge Time Sec.	PSI	H"	Dia."	Included Bracket	Wt. lbs.	Price /Each
SAQ814	SFABC110STVB	2.5	1A:10BC	8 - 10	12-14	150	15 1/2	3 1/8	Vehicle	4 1/4	52.70
SA445	WBDL-ABC310LV	5	3A:10BC	8 - 10	13 - 14	195	16	4 1/4	Wall	10 1/2	60.20
SC946	SFABC310VB	5	3A:10BC	8 - 10	13 - 14	195	16	4 1/4	Wall & Vehicle	10 1/2	67.50
SED109*	SFABC340VB	5	3A:40BC	8 - 10	13 - 14	195	16	4 1/4	Wall & Vehicle	10 1/2	70.00
SA443	SFABC680	10	6A:80BC	10 - 15	14 - 16	235	21 1/4	5 1/8	Wall	19 1/4	98.30
SA444	SFABC1020	20	10A:120BC	10 - 15	20 - 22	235	24	7 1/8	Wall	35 1/4	183.00
SED110	SFABC30	30	10A:120BC	10 - 15	28	195	30 3/4	7 1/8	Wall	50 1/3	374.00

*Meets requirements for forklifts

ACCESSORIES

Model No.	Mfg. No.	Description	Fits	Price/Each	Model No.	Mfg. No.	Description	Fits	Price/Each
SC951	C160738	Wall Hook	5 lbs.	2.84	SA442	UP2	Vehicle Bracket	2.5 lbs.	5.93
SC952	C160752	Wall Hook	10 lbs.	2.95	SC955	UB5	Vehicle Bracket	5 lbs.	5.93
SC953	C160791	Wall Hook	20 lbs.	3.01					

ALUMINUM CYLINDER CARBON DIOXIDE (CO₂) FIRE EXTINGUISHERS

- Well suited for corrosive environments
- Industrial-strength aluminum cylinder is up to 30% lighter than steel
- Stainless steel hose band
- Strong impact-resistant horn
- Bar-coded label
- Easy to service
- Comes with wall hook
- ULC listed



Model No.	Mfg. No.	Cap. lbs.	Rating	Range Feet	Discharge Time Sec.	H"	Dia."	Wt. lbs.	Price /Each
SAJ098	SF-5C02	5	5BC	6-12	10	17 1/4	5 3/4	13 1/4	244.00
SAJ099	SF-10C02	10	10BC	6-12	10	19 3/4	6 3/4	27	377.00
SAJ100	SF-15C02	15	10BC	6-12	15	26 3/4	6 3/4	37	478.00
SAL344	SF-20C02	20	10BC	6-12	20	26 3/4	8	48 1/8	529.00

ACCESSORIES

Model No.	Mfg. No.	Description	Fits	Price/Each	Model No.	Mfg. No.	Description	Fits	Price/Each
SAM953	SF5WH	Wall Hook	5 lbs.	2.02	SAP900	HDVB-2	Vehicle Bracket	5 lbs.	49.90
SAM954	SF1015WH	Wall Hook	10-15 lbs.	2.02	SAM957	HDVB-3	Vehicle Bracket	10 lbs.	55.20
SAM955	SF20WH	Wall Hook	20 lbs.	2.30	SED313	HDVB-4	Vehicle Bracket	15 lbs.	132.00

K CLASS WET CHEMICAL EXTINGUISHERS

- Brass valve construction
- Specially designed and tested to address fires in restaurants and commercial fryers
- Very effective on cooking oil and grease fires
- Ideal for restaurants, kitchens, cafeterias, food courts, and other locations with high temperature cooking materials
- Nozzle designed to prevent splashing
- Designed to be used in conjunction with a kitchen suppression system



Model No.	Mfg. No.	Cap. Liters	Rating	Range Feet	Discharge Time Sec.	PSI	H"	Dia."	Included Bracket	Wt. lbs.	Price /Each
SED438	SF-6LK	6	1-A:K	10-12	60	100	21 1/2	7	Wall	25	297.00