



ELECTRICAL TAPE

aurora tools

- Vinyl plastic
- Excellent recovery, molds snugly to any surface
- Ideal for electrical splicing and insulation; protection against solvents and corrosion
- For use between -7°C and 80°C
- Thickness: 7 mils • CSA approved



Priced per Roll

Model No.	Colour	Dimensions	Price /Each
XE890	Black	3/4" x 60' (19 mm x 18 m)	1.00
XH383	Red	3/4" x 60' (19 mm x 18 m)	1.10
XH384	Green	3/4" x 60' (19 mm x 18 m)	1.10

Model No.	Colour	Dimensions	Price /Each
XH385	Blue	3/4" x 60' (19 mm x 18 m)	1.10
XH386	White	3/4" x 60' (19 mm x 18 m)	1.10
XH387	Yellow	3/4" x 60' (19 mm x 18 m)	1.10

COLOURFLEX™ TAPE

- General purpose colour coding vinyl tape
- Thickness: 7 mils



3M

Priced per Roll

Model No.	Colour	Dimensions	Roll /Case	Price /Each
XC316	Blue	3/4" x 60'	100	1.36
XC317	Green	3/4" x 60'	100	1.36
XC318	Red	3/4" x 60'	100	1.36
XC319	White	3/4" x 60'	100	1.36
XC320	Yellow	3/4" x 60'	100	1.36
XC321	Orange	3/4" x 60'	100	1.36

SCOTCH® SUPER 33+ VINYL TAPE

- All weather, premium grade vinyl tape for primary insulation up to 600 V or protective jacketing for low/medium voltage cable splices and repairs
- Aggressive adhesive and elastic backing ensures easy conformation to irregular surfaces for moisture tight electrical and mechanical protection
- Will perform in a continuous temperature environment up to 220°F (105°C)
- Conformable for cold weather applications: 0°F (-18°C)
- Thickness: 7 mil
- Colour: Black
- UL and CSA approved



3M

Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each
PC693	3/4" x 66' (19 mm x 20.1 m)	100	8.06

TEMFLEX™ ELECTRICAL TAPE

- General purpose, flexible vinyl tape designed for indoor or short term use and bundling
- Temperature rating: 176°F/80°C
- Colour: Black
- Thickness: 7 mil
- UL and CSA approved



3M

Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each
PC695	3/4" x 60' (19 mm x 18.3 m)	100	1.28

SCOTCH® SUPER 88 VINYL TAPE

- All weather, premium grade vinyl tape for primary insulation up to 600 V or protective jacketing for low/medium voltage cable splices
- Aggressive adhesive and elastic backing ensures easy conformation to irregular surfaces for moisture tight electrical and mechanical protection
- Will perform in a continuous temperature environment up to 220°F (105°C)
- Conformable for cold weather applications: 0°F (-18°C)
- Thickness: 7 mil
- Colour: Black
- UL and CSA approved



3M

Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each
PC694	3/4" x 66' (19 mm x 20.1 m)	100	9.01

SCOTCH® 130C LINERLESS RUBBER SPLICING TAPE

- Highly conformable, linerless self-bonding ethylene propylene rubber (EPR) tape for insulating all solid dielectric cables up to 69 kV
- Excellent thermal dissipation of splice heat
- Meets industry specifications, excellent physical and electrical properties
- Immediate moisture sealing and void-free buildups
- Rated up to 194°F (90°C) continuous operation and up to 266°F (130°C) short-term overload service
- Having no liner makes jobs easier and saves time
- Thickness: 30 mils




3M

Priced per Roll

Model No.	Dimensions	Rolls/Case	Price/Each
AF284	3/4" x 30'	24	20.10
XC323	1" x 30'	24	26.80
XH307	1-1/2" x 30'	12	40.10

SCOTCH® 35 COLOUR CODING VINYL TAPE

- Premium grade vinyl electrical colour-coding tape for phase and job identification and safety
- Heavy-duty, premium grade
- Temperature rating: 220°F/105°C
- Thickness: 7 mil
- Colour: Black
- UL and CSA approved



3M

Priced per Roll

Model No.	Colour	Dimensions	Rolls /Case	Price /Each
PC696	Blue	1/2" x 20'	100	3.01
PC720	Green	1/2" x 20'	100	3.01
PC721	Red	1/2" x 20'	100	3.01
PC722	White	1/2" x 20'	100	3.01
PC723	Yellow	1/2" x 20'	100	3.01
XC309	Orange	1/2" x 20'	100	3.01
PE118	Blue	3/4" x 66'	100	8.20
PE120	Green	3/4" x 66'	100	8.20
XC312	Red	3/4" x 66'	100	8.20
PE119	White	3/4" x 66'	100	8.20
XC314	Yellow	3/4" x 66'	100	8.20
XC315	Orange	3/4" x 66'	100	8.20

SCOTCH® 27 GLASS CLOTH ELECTRICAL TAPE

- Ideal for electrical maintenance applications
- Woven glass cloth tape with a rubber thermosetting pressure-sensitive adhesive
- Edge-tear resistant, conformable, abrasion resistant
- For use as a coil cover, anchor, banding and core, layer and crossover insulation, and for heat-stable insulation for furnace and oven controls, motor leads, and switches
- Thickness: 7 mils
- UL recognized 130°C/266°F



3M

Priced per Roll

Model No.	Dimensions	Rolls/Case	Price/Each
XH289	1/2" x 66' (12 mm x 20.1 m)	10	18.43
XC322	3/4" x 66' (19 mm x 20.1 m)	50	27.88