

LIFTING, POSITIONING & STACKING

DYNAMIC LIFT™ MAGNETS

- Lifting Capacity: 150 lbs.
- Weight: 6.1 lbs.
- Powerful rare earth permanent lift magnets
- Top rotating locking On/Off handle
- Lifts flat or round loads horizontally
- Lifts flat loads vertically
- Heat resistant up to 180° F (82° C)
- 3:1 Design factor
- **Conforms to ASME B30.20 standards**

MAG-MATE™

LU436



Model No.	Overall Dimensions				Lift lb	Wt. lb	Price /Each
	L" x W" x H"	L" x W" x H"	L" x W" x H"	L" x W" x H"			
LU436	5 x 2 x 9				150	6.1	549.00
LU437	6 1/2 x 4 x 9 1/4				334	13.3	1259.00

CREATIVE LIFT® MAGNETS

- Permanent lift magnets are ideal for handling steel plates, die castings, forgings etc.
- They eliminate the need for clamping devices, slings or chains
- One person can perform operations previously calling for two or more people
- Non-marring roller cam release
- Durable stainless steel casing
- 3:1 design factor
- **Conforms to ASME B30.20 standards.**

MAG-MATE™



Model No.	Dimensions				Magnet		Holding Capacity lbs.	Price /Each
	L" x W" x H"	L" x W" x H"	L" x W" x H"	L" x W" x H"	H" L"	L"		
LS708	7 3/4 x 7 1/4 x 6 3/4				2 1/2	4	400	779.00
LS709	10 3/4 x 7 1/4 x 6 3/4				2 1/2	7	1000	1049.00
LS710	14 3/4 x 7 1/4 x 6 3/4				2 1/2	10 1/2	1500	1329.00
LT271	15 x 10 1/2 x 7				2 1/2	11 1/4	2200	1889.00
LS711	19 1/4 x 10 1/2 x 7				2 1/2	15 1/4	3000	2629.00

HOLDING VALUE & MAX. SHEET LENGTH (IN FEET) FOR SPECIFIED MATERIAL THICKNESS

Model No.	3/16"		1/4"		1/2"		1"		2"	
	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length
LS708	400	6	400	6	400	8	400	10	400	10
LS709	600	6	900	6	1000	8	1000	10	1000	10
LS710	800	6	1000	6	1500	8	1500	10	1500	10
LT271	800	6	1064	6	2000	8	2200	10	2200	10
LS711	800	6	1100	6	2700	8	3000	10	3000	10

WINCH OPERATED TRUCK JIB CRANE

- Lift items from ground to truck bed height
- Install in pick up truck beds
- Telescopic boom design with manual hydraulic hand pump to pivot boom up and down
- Manual cable winch to lift and lower loads
- Friction brake winch locks automatically when operator turns the handle counter clockwise to lower load
- Unit comes with one fixed hook, one chain slot lock, and one cable hook with latch



Model No.	Boom Extended Capacity	Boom Retracted Capacity	Cable Winch Capacity	Boom Extended Reach	Boom Retracted Reach	Extended Lift Range	Retracted Lift Range	Finish	Cable Usage Length	Price /Each
LU494	500 lbs.	1000 lbs.	500 lbs.	51"	34-3/4"	0"-102"	10"-89-1/2"	Yellow Coated	9'	658.00
LU495	1000 lbs.	2000 lbs.	500 lbs.	44"	30"	0"-86-1/2"	13-1/2"-77-1/2"	Yellow Coated	9'	740.00
LU496	500 lbs.	1000 lbs.	500 lbs.	52"	30-1/2"	0"-99"	13-1/2"-84"	Galvanized	20' w/Dia. 1/4"	956.00
LU497	1000 lbs.	2000 lbs.	500 lbs.	52"	31"	0"-97"	13-1/2"-86"	Galvanized	20' w/Dia. 1/4"	1162.00

POWERLIFT® MAGNETS

- Compact yet powerful rare earth lift magnets can be used on flat or round surfaces and contain an internal release on/off device that does not contact or damage the surface of the part being lifted
- Permanent magnetic lifts eliminate the fear of dropping the load being lifted due to power failures
- 3:1 design factor
- **Conforms to ASME B30.20 standards**

MAG-MATE™



Model No.	Capacity lbs.		Minimum Diameter"	Dimensions				Handle"	Wt. lbs.	Price /Each
	Flat	Round		L" x W" x H"	L" x W" x H"	L" x W" x H"	L" x W" x H"			
LS712	250	125	2	5 x 2 5/8 x 6 5/8	5 7/8	5 7/8	5 7/8	7	7	459.00
LS713	800	400	3	7 7/8 x 3 5/8 x 8 7/8	6 7/8	6 7/8	6 7/8	22	22	949.00
LS714	1600	800	4	10 3/4 x 4 7/8 x 8 7/8	6 3/4	6 3/4	6 3/4	53	53	1549.00
LS715	2500	1250	5	12 5/8 x 7 1/8 x 8 7/8	10 1/8	10 1/8	10 1/8	110	110	2529.00

HOLDING VALUE & MAX. SHEET LENGTH (IN FEET) FOR SPECIFIED MATERIAL THICKNESS

Model No.	1/4"		1/2"		3/4"		1"		3"	
	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length
LS712	180	6	250	6	250	6	250	10	250	10
LS713	270	6	615	6	800	6	800	10	800	10
LS714	N/A	-	800	6	1600	6	1600	10	1600	10
LS715	N/A	-	N/A	-	N/A	-	1300	10	2500	10

BASICLIFT MAGNETS

- Permanent lift magnet for a broad range of lifting applications
- Full width cam release
- Large lift lug
- Light weight design
- Durable stainless steel casing
- Heat resistant up to 300°F (148°C)
- 2:1 design factor

MAG-MATE™





Model No.	Overall Dimensions				Lift lb	Wt. lb	Price /Each
	L" x W" x H"	L" x W" x H"	L" x W" x H"	L" x W" x H"			
LT372	7 1/2 x 5 5/8 x 5 1/2				400	13	619.00
LT373	11 x 5 5/8 x 5 1/2				1000	18	869.00
LT374	14 1/2 x 5 5/8 x 5 1/2				1500	28	1159.00

HOLDING VALUE & MAX. SHEET LENGTH (IN FEET) FOR SPECIFIED MATERIAL THICKNESS

Model No.	3/16"		1/4"		1/2"		3/4"		1"	
	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length	Cap lbs.	Length
LT372	375	6	400	6	400	8	400	8	400	10
LT373	725	6	800	6	975	8	1000	8	1000	10
LT374	875	6	1000	6	1400	8	1500	8	1500	10



KLETON



CANADA'S LEADING MATERIAL HANDLING SUPPLIER