

COMPRESSORS

QUIET SERIES AIR COMPRESSOR

- Ideal for indoor use, including trim, cabinetry, hobby and DIY applications
- Oil-free, dual cylinder design requires no day to day maintenance and offers reduced operating costs
- Low amperage draw reduces incidents of tripped breakers and voltage drops that cause premature motor failure
- Lower RPM operating speed generates less heat for maximum motor and pump life
- Air pressure regulator enables easy adjustment of line pressure
- Complete roll cage design protects motor, pump and switch from damage during storage, transport and operation
- Protective fence for operator protection against accidental contact with hot surfaces
- Integrated cord wrap for operator convenience
- Fast recovery time suitable for professional applications
- Lightweight, compact design ideal for on-site applications and operator convenience



UAJ414



UAJ415



UAJ416



Model No.	Mfg. No.	Horse Power	CFM	Voltage /Phase	Tank Capacity	Max. PSI	Sound Level (dBA)	Price /Each
UAJ414	MAC100Q	0.5 HP	0.7 at 90 PSI	120/1	1 Gal (1.2 US Gal)	135	58	259.00
UAJ415	MAC210Q	1.0 HP	2 at 90 PSI	120/1	2 Gal (2.4 US Gal)	135	60	329.00
UAJ416	MAC320Q	1.5 HP	52.6 at 90 PSI	120/1	3 Gal (3.6 US Gal)	135	60	429.00

2.5 HP ELECTRIC AIR COMPRESSORS

- Oil lubricated for cooler operation and reduced noise
- High output cast iron pump with large bore cylinder
- Low amp draw reduces incidences of tripped breakers and voltage drop that can cause premature motor failure
- Air pressure regulator enables adjustments of line pressure
- Roll cage construction to protect components

Model No. TLZ558 Mfg. No. MAC2400
Price/Each \$469.00

Horsepower: 2.5 HP
Tank Size: 2 x 2.1 gal.
Power Supply: 120 V, 12.3 A,
CFM @90 PSI: 4.2 CFM
Max PSI: 130
Dimensions: 19 3/8" L x 18 3/4" W x 18" H
Weight: 77 lbs.
Includes: 1/4" quick coupler,
air filter, compressor oil



3 HP ELECTRIC AIR COMPRESSORS

- Oil lubricated for cooler operation and reduced noise
- High output cast iron pump, delivers maximum performance
- Designed especially for framing nailers
- Air pressure regulator enables adjustments of line pressure to tool
- Stores 50' of 3/8" air hose with handle folded or upright

Model No. TLZ557 Mfg. No. MAC5200
Price/Each \$559.00

Horsepower: 3.0 HP
Tank Size: 5.2 gal.
Power Supply: 120 V, 13.8 A,
CFM @90 PSI: 6.5 CFM
Max PSI: 140
Dimensions: 29" L x 19" W x 19 1/2" H
Weight: 88 lbs.
Includes: 1/4" quick coupler,
air filter, compressor oil



AIR COMPRESSOR

- Oil lubricated pump for cooler operation and reduced noise
- High output V-twin cast iron pump runs cooler than inline pumps and delivers maximum performance and operational life
- Big Bore™ cylinder and piston feature high output at lower RPM with reduced heat buildup, less noise and longer operational life
- Automatic idle control minimizes fuel consumption and maximizes service life
- Includes: (2) Quick couplers, (1) Spark plug
- Horse Power: 5.5 HP
- CFM: 12.5 at 100 PSI
- Electric/Gas: Gas
- Tank Capacity: 8.33 Gal. (10 US Gal)
- Max. PSI: 130
- Sound Level (dBA): 89
- Engine: 4-Stroke Honda GX160

Model No. UAF023
Mfg. No. MAC5501G
Price/Each \$1609.00

