

COMPRESSOR ACCESSORIES

FILTERS/REGULATORS/LUBRICATORS (GAUGE INCLUDED)

- High-flow capacity reduces costly pressure drop
- Compact size allows greater design flexibility
- **Heavy-Duty:** High-capacity performance featuring rugged design for the most demanding applications

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA689	1/4	31	150	0-125	125	Manual	Polyurethane	1.5	7 1/16	4 25/32	291.00
TA690	1/4	31	150	0-125	125	Auto	Polyurethane	1.5	7 1/16	4 25/32	302.00
TA693	1/4	23	150	0-125	125	Manual	Polyurethane	3.8	8 1/16	6 35/64	330.00
TA694	1/4	23	150	0-125	125	Auto	Polyurethane	3.8	8 1/16	6 35/64	377.00
TA697	3/8	45	150	0-125	125	Manual	Polyurethane	3.8	8 1/16	6 35/64	330.00
TA698	3/8	45	150	0-125	125	Auto	Polyurethane	3.8	8 1/16	6 35/64	377.00
TA701	1/2	60	150	0-125	125	Manual	Polyurethane	3.8	8 1/16	6 35/64	330.00
TA702	1/2	60	150	0-125	125	Auto	Polyurethane	3.8	8 1/16	6 35/64	377.00
TA703	1/2	60	250	0-125	150	Manual	Zinc	3.8	8 1/16	6 35/64	364.00
STANDARD DUTY MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA705	1/2	110	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	8 1/16	409.00
TA706	1/2	110	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	8 1/16	456.00
TA709	3/4	125	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	8 1/16	419.00
TA710	3/4	125	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	8 1/16	465.00
HEAVY-DUTY, 5-MICROMETRES FILTRATION											
TA713	1	240	250	0-125**	125	Manual	Zinc	16	11	15 3/4	755.00
TA714	1	240	175	0-125**	125	Auto	Zinc	16	11	15 3/4	774.00
TA717	1 1/2	400	250	0-125**	125	Manual	Zinc	16	11 11/32	16 1/2	881.00
TA718	1 1/2	400	175	0-125**	125	Auto	Zinc	16	11 11/32	16 1/2	901.00

*Also available 0-25 PSI, 0-60 PSI, 0-250 PSI **Also available 0-250 PSI



FILTERS/REGULATORS & COALESCING FILTERS (GAUGE INCLUDED)

- High-flow capacity reduces costly pressure drop
- Compact size allows greater design flexibility
- Lightweight construction for ease of installation

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Reduced Pressure Range PSI	Max Temp. °F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA743	1/4	20	150	0-125	125	Manual	Polyurethane	1.5	7 3/64	3 13/64	263.00
TZ031	1/4	20	150	0-125	125	Auto	Polyurethane	1.5	7 3/64	3 13/64	283.00
TA745	1/4	40	150	0-125	125	Manual	Polyurethane w/Guard	3.8	8 1/16	4 23/64	366.00
TA746	1/4	40	150	0-125	125	Auto	Polyurethane w/Guard	3.8	8 1/16	4 23/64	460.00
TA747	1/4	40	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	396.00
TA748	1/4	40	175	0-125	125	Auto	Zinc	3.8	8 1/16	4 23/64	497.00
TA749	3/8	43	150	0-125	125	Manual	Polyurethane w/Guard	3.8	8 1/16	4 23/64	366.00
TA750	3/8	43	150	0-125	125	Auto	Polyurethane w/Guard	3.8	8 1/16	4 23/64	460.00
TA751	3/8	43	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	395.00
TA752	3/8	43	175	0-125	125	Auto	Zinc	3.8	8 1/16	4 23/64	498.00
TA761	1/2	43	150	0-125	125	Manual	Polyurethane w/Guard	3.8	8 1/16	4 23/64	366.00
TA762	1/2	43	150	0-125	125	Auto	Polyurethane w/Guard	3.8	8 1/16	4 23/64	460.00
TA763	1/2	43	250	0-125	150	Manual	Zinc	3.8	8 1/16	4 23/64	396.00
TA764	1/2	43	175	0-125	125	Auto	Zinc	3.8	8 1/16	4 23/64	497.00
STANDARD DUTY MODULAR DESIGN, 5-MICROMETRES FILTRATION											
TA753	1/2	85	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	5 3/8	434.00
TA754	1/2	85	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	5 3/8	510.00
TA755	1/2	85	250	0-125*	150	Manual	Zinc	8.5	10 21/64	5 3/8	477.00
TA756	1/2	85	175	0-125*	125	Auto	Zinc	8.5	10 21/64	5 3/8	552.00
TA757	3/4	85	150	0-125*	125	Manual	Polyurethane w/guard	8.5	10 21/64	6 1/16	459.00
TA758	3/4	85	150	0-125*	125	Auto	Polyurethane w/guard	8.5	10 21/64	6 1/16	562.00
TA759	3/4	85	250	0-125*	150	Manual	Zinc	8.5	10 21/64	6 1/16	509.00
TA760	3/4	85	175	0-125*	125	Auto	Zinc	8.5	10 21/64	6 1/16	609.00

*Also available 0-25 PSI, 0-60 PSI, 0-250 PSI

