

FILTERS

- High flow capacity reduces costly pressure drop
- Compact size allows greater design flexibility
- Lightweight for ease of installation

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Max Temp.°F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
MINI MODULAR DESIGN, 5-MICROMETRES FILTRATION										
TA590	1/4	31	150	125	Manual	Polyurethane	1.5	5 3/64	1 19/32	78.40
TA591	1/4	31	150	125	Auto	Polyurethane	1.5	5 3/64	1 19/32	88.60
TA592	1/4	31	250	150	Manual	Zinc	1.5	5 3/64	1 19/32	89.40
TA593	1/4	31	175	150	Auto	Zinc	1.5	5 3/64	1 19/32	99.50
COMPACT MODULAR DESIGN, 5-MICROMETRES FILTRATION										
TA594	1/4	42	150	125	Manual	Polyurethane w/guard	3.8	6 3/16	2 3/16	117.00
TA595	1/4	42	150	125	Auto	Polyurethane w/guard	3.8	6 3/16	2 3/16	167.00
TA598	3/8	64	150	125	Manual	Polyurethane w/guard	3.8	6 3/16	2 3/16	117.00
TA599	3/8	64	150	125	Auto	Polyurethane w/guard	3.8	6 3/16	2 3/16	167.00
TA602	1/2	68	150	125	Manual	Polyurethane w/guard	3.8	6 3/16	2 3/16	117.00
TA603	1/2	68	150	125	Auto	Polyurethane w/guard	3.8	6 3/16	2 3/16	167.00
STANDARD DUTY MODULAR DESIGN, 5-MICROMETRES FILTRATION										
TA606	1/2	115	150	125	Manual	Polyurethane w/guard	8.5	7 63/64	2 11/16	152.00
TA607	1/2	115	150	125	Auto	Polyurethane w/guard	8.5	7 63/64	2 11/16	197.00
TA610	3/4	148	150	125	Manual	Polyurethane w/guard	8.5	7 63/64	3 1/32	152.00
TA611	3/4	148	150	125	Auto	Polyurethane w/guard	8.5	7 63/64	3 1/32	202.00
HEAVY-DUTY, 40-MICROMETRES FILTRATION										
TA614	1	240	250	150	Manual	Zinc	16	8 23/32	4 1/16	327.00
TA615	1	240	175	125	Auto	Zinc	16	8 23/32	4 1/16	372.00
TA616	1 1/2	450	250	150	Manual	Zinc	16	9 29/64	5 3/16	368.00
TA617	1 1/2	450	175	125	Auto	Zinc	16	9 29/64	5 3/16	397.00
TA618	2	1200	250	150	Manual	Zinc	16	13 1/32	6 3/16	909.00
TA619	2	1200	175	125	Auto	Zinc	16	13 1/32	6 3/16	948.00



Mini Design
w/Polyurethane Bowl
TA590



Compact Design w/
Polyurethane
TA594



Heavy-Duty Design
w/Zinc Bowl
TA614

COALESCING FILTERS

Highly efficient filters designed for applications requiring the removal of all solid particles greater than 0.01 micron, together with 99.999% of the oil and water aerosols.

TOPRING

Model No.	NPT Size"	Max SCFM @ 100 PSI	Max PSI	Max Temp.°F	Drain Type	Bowl Type	Bowl Cap. oz.	H"	W"	Price /Each
COMPACT MODULAR DESIGN, 0.01-MICROMETRES FILTRATION										
TA765	1/4	20	150	125	Manual	Polyurethane	1.5	5 3/64	1 19/32	137.00
TA766	1/4	20	150	125	Auto	Polyurethane	1.5	5 3/64	1 19/32	148.00
TA767	1/4	20	250	150	Manual	Zinc	1.5	5 3/64	1 19/32	149.00
TA769	1/4	43	150	125	Manual	Polyurethane w/guard	3.8	6 3/16	2 3/16	213.00
TA770	1/4	43	150	125	Auto	Polyurethane w/guard	3.8	6 3/16	2 3/16	267.00
TA771	1/4	43	250	150	Manual	Zinc	3.8	6 3/16	2 3/16	229.00
TA772	1/4	43	175	125	Auto	Zinc	3.8	6 3/16	2 3/16	282.00
TA777	3/8	43	150	125	Manual	Polyurethane w/guard	3.8	6 3/16	2 3/16	213.00
TA778	3/8	43	150	125	Auto	Polyurethane w/guard	3.8	6 3/16	2 3/16	267.00
TA779	3/8	43	250	150	Manual	Zinc	3.8	6 3/16	2 3/16	229.00
TA780	3/8	43	175	125	Auto	Zinc	3.8	6 3/16	2 3/16	282.00
TA773	1/2	43	150	125	Manual	Polyurethane w/guard	3.8	6 3/16	2 3/16	213.00
TA774	1/2	43	150	125	Auto	Polyurethane w/guard	3.8	6 3/16	2 3/16	267.00
TA775	1/2	43	250	150	Manual	Zinc	3.8	6 3/16	2 3/16	229.00
TA776	1/2	43	175	125	Auto	Zinc	3.8	6 3/16	2 3/16	282.00
STANDARD DUTY MODULAR DESIGN, 0.01-MICROMETRES FILTRATION										
TA781	1/2	85	150	125	Manual	Polyurethane w/guard	8.5	7 63/64	2 11/16	239.00
TA782	1/2	85	150	125	Auto	Polyurethane w/guard	8.5	7 63/64	2 11/16	287.00
TA783	1/2	85	250	150	Manual	Zinc	8.5	7 63/64	2 11/16	264.00
TA784	1/2	85	175	125	Auto	Zinc	8.5	7 63/64	2 11/16	323.00
TA785	3/4	85	150	125	Manual	Polyurethane w/guard	8.5	7 63/64	3 1/32	293.00
TA786	3/4	85	150	125	Auto	Polyurethane w/guard	8.5	7 63/64	3 1/32	340.00
TA787	3/4	85	250	150	Manual	Zinc	8.5	7 63/64	3 1/32	338.00
TA788	3/4	85	175	125	Auto	Zinc	8.5	7 63/64	3 1/32	383.00



Compact Design
w/ Polyurethane Bowl
TA765



Compact Design w/
Polyurethane
TA769