

END BRUSHES

Especially suited for use on portable air and electric tools, CNC and robotic equipment, the end brush is designed for work where space limitations are a factor. In most applications, higher speeds (up to 25 000 RPM) are required for effective brushing action. Osborn® end brush fill materials include carbon and stainless steels, brass, natural fibre, abrasive nylon, and TY® elastomer encapsulated wire.

OD - OUTSIDE DIAMETER

Standard Osborn® end brushes are made with outside diameters from 3/16" through 3". For larger surfaces or "surround" applications, multiple brushes may be clustered. As a guide, add 1/8" to brush O.D. to get overall O.D.

T - TRIM LENGTH

Shorter brush section provides stiffness and faster cutting. Longer filaments have more flexibility for irregular surfaces.

OAL - OVERALL LENGTH

Distance from end of brush part to end of shank.

S - SHANK DIAMETER

All standard end brushes have 1/4" diameter shank. Miniature end brushes have 1/8" diameter shank.



CRIMPED WIRE END BRUSHES

- Engineered to operate at high speeds
- Applications:** Rubber and Plastic Mold Cleaning/Cleaning Pipe I.D./Removing Rust, Weld Scale and Spatter/Cleaning Castings/Burr Removal/Rubber Flash Removal/Carbon Removal/Spot Facing/Cleaning and Finishing Recessed Areas



WITH 1/4" SHANK

Model No.	Brush Dia."	O.A. Length"	Wire Gauge"	Trim Length"	Max RPM	Price /Each
STEEL						
BX374	1/2	2 3/4	0.0104	1	25 000	8.89
BX375	1/2	2 3/4	0.02	1	25 000	8.49
BX378	3/4	2 3/4	0.02	1	20 000	12.40
STAINLESS						
BX359	1/2	2 3/4	0.0104	1	25 000	15.40
BX360	1/2	2 3/4	0.014	1	25 000	13.20

CRIMPED WIRE END BRUSHES

- Ideal for flash, scale, rust, corrosion and paint removal
- Softer impact and more flexible than knotted brushes
- Great tool for polishing, edge blending and surface preparation
- Efficient, light cleaning of small hard-to-reach surface areas



Model No.	Brush Dia."	Fill Dia."	Shank Size"	Fill Length"	Max RPM	Price /Each
STEEL						
NU447	1/2	0.005	1/4	1	20 000	12.62
TT316	1/2	0.014	1/4	1	20 000	12.07
NU449	3/4	0.005	1/4	1	20 000	11.06
NU451	1	0.005	1/4	1	20 000	15.12
TT317	1	0.014	1/4	1	20 000	15.18
STAINLESS						
NU448	1/2	0.005	1/4	1	20 000	17.32
TC135	3/4	0.014	1/4	1	20 000	12.97
NU450	3/4	0.006	1/4	1	20 000	22.45
NU452	1	0.005	1/4	1	20 000	33.66

KNOT WIRE END BRUSHES

- Ideal for flash, scale, rust, corrosion and paint removal
- Great tool to reach into holes and hard to reach areas
- More aggressive brushing action than crimped brushes
- Low flexibility knotted wire for high impact brushing



Model No.	Brush Dia."	Fill Dia."	Shank Size"	Fill Length"	Max RPM	Price /Each
STEEL						
NU456	1/2	0.014	1/4	1	22 000	27.44
NU457	3/4	0.014	1/4	1	22 000	28.51
MLP989	1	0.012	1/4	1	25 000	20.05
TT300	1	0.014	1/4	1	25 000	18.79
TC134	1	0.020	1/4	1	25 000	18.14
STAINLESS						
NU453	1	0.012	1/4	1	25 000	34.30
NU454	1	0.014	1/4	1	25 000	37.75
NU455	1	0.020	1/4	1	25 000	37.58

KNOT WIRE END BRUSHES

Rugged brushing tools designed with the finest wire to offer efficient usage for a wide variety of tough cleaning and maintenance applications; can be used on CNC equipment. Available with steel, stainless steel and brass wire. Certain styles are available in clamshell packaging.

- Applications:** Spot Cleaning or Facing/Removal of Slag, Rust or Scale/Cleaning Pipe I.D./Deburring or Flash Removal/Cleaning of Dies, Moulds and Tooling/Pipeline Cleaning



WITH 1/4" SHANK

Model No.	Brush Dia."	O.A. Length"	Wire Gauge"	Trim Length"	Max RPM	Price /Each
STEEL						
BX350	1/2	2 3/4	0.014	1 1/8	22 000	19.80
BX353	3/4	2 3/4	0.014	1 1/8	20 000	19.80
BX357	1	2 3/4	0.014	1	20 000	22.00
STAINLESS						
BX481	1/2	2 3/4	0.014	1 1/8	22 000	19.80
BX484	3/4	2 3/4	0.014	1 1/8	20 000	22.00
BX487	1	2 3/4	0.014	1	20 000	27.10

SCUF-GUARD COATED BRUSHES

- Made with a durable elastomer layer on the cup to help prevent accidental scratches or markings on the work surface during operation
- Stainless steel wire



Model No.	Brush Dia."	Brush Length"	O.A. Length"	Fill Dia."	Trim Length"	Max RPM	Price /Each
BX364	1/2	1 1/8	2 3/4	0.006	1 1/8	22 000	34.90
BX366	1/2	1 1/8	2 3/4	0.014	1 1/8	22 000	28.30
BX367	3/4	1 1/8	2 3/4	0.006	1 1/8	20 000	39.40
BX369	3/4	1 1/8	2 3/4	0.014	1 1/8	20 000	29.40
BX370	1	1	2 3/4	0.006	1 1/8	20 000	48.20
BX372	1	1	2 3/4	0.014	1	20 000	38.70