

GAS WELDING OUTFITS & ACCESSORIES

SINGLE STAGE REGULATORS NO. 25

- One-piece encapsulated seat design with an internal filter and a PTFE Teflon® seat
- Chrome-plated bonnet with forged brass body
- 2" dual scale gauges
- Gauge guards sold separately



Model No.	Mfg. No.	Gas	Max Inlet PSIG	Delivery Pressure Range, PSIG	Delivery Pressure Gauge, PSIG	Supply Pressure Gauge, PSIG	Inlet Connection	Outlet Connection	Price /Each
TTT920	3000380	Acetylene	500	0-15	30	400	CGA510	9/16"-18 LH	319.00
TTT921	3000450	Propane*	500	0-50	60	400	CGA510P	9/16"-18 LH	319.00
TTT922	3000510	Oxygen	3000	0-100	150	4000	CGA540	9/16"-18 RH	319.00
TTT923	3000540	Ar, N ₂ , He	3000	0-100	150	4000	CGA580	9/16"-18 RH	319.00
TTT924	3000550	Industrial Air	3000	0-100	150	4000	CGA590	9/16"-18 RH	319.00
TTT925	3000806	N ₂	3000	0-200	400	4000	CGA580	9/16"-18 RH	399.00

GAUGE GUARDS

TTT926	4300140	Fuel Gas	67.10
TTT927	4300139	Oxygen	67.10

*Regulator designated for propane service can be used with any of the other welding grade liquid petroleum gases. NOT FOR USE WITH ACETYLENE.

152 SERIES - SINGLE STAGE REGULATORS

- Designed for medium-duty gas welding, cutting and heating applications
- Body and housing cap are machined from class "A" brass bar stock
- Self re-seating external safety pressure relief valve on oxygen models
- Stem type seat assembly for more reliable performance
- 2" gauges for easy reading
- 2" diaphragm
- UL listed



Model No.	Mfg. No.	Gas Service	Max Inlet/Delivery Pressure (PSI)	Inlet Gauge	Outlet Gauge	Inlet Connection	Outlet Connection	Price /Each
331-3575	152X-80	Oxygen	3000/4-80	2", 4000 PSI	2", 100 PSI	CGA540	9/16"-18 RH (M)	209.00
331-3585	152Y-15	Acetylene	400/2-15	2", 400 PSI	2", 30 PSI, RL	CGA510	9/16"-18 LH (M)	209.00



153 SERIES - SINGLE STAGE REGULATORS

- Designed for heavy-duty gas welding, cutting and heating applications
- 2 1/2" gauges for easy reading
- 3 1/4" stainless steel diaphragm for accurate pressure delivery
- Delrin cap bushing for smooth adjustments
- Stem type seat assembly for more reliable performance
- Body and housing cap machined from class "A" brass bar stock
- Self re-seating external pressure relief valve on oxygen model
- Sintered bronze inlet filter
- UL listed



Model No.	Mfg. No.	Gas Service	Max Inlet/Delivery Pressure (PSI)	Inlet Gauge	Outlet Gauge	Inlet Connection	Outlet Connection	Price /Each
331-3665	153X-125	Oxygen	3000/5-125	2 1/2", 4000 PSI	2 1/2", 200 PSI	CGA540	9/16"-18 RH (M)	409.00
331-3675	153Y-15	Acetylene	400/2-15	2 1/2", 400 PSI	2 1/2", 30 PSI, RL	CGA510	9/16"-18 LH (M)	409.00



452 SERIES - SINGLE STAGE REGULATORS

- Designed for medium to heavy-duty gas welding, cutting and heating applications; the "Horse" is a Harris' style regulator
- 2 3/4" diaphragm and a Victor® style seat mechanism
- Forged brass body
- Self re-seating external pressure relief valve on oxygen, inert gases and carbon dioxide models
- Sintered bronze inlet filter
- 2" gauges for easy reading
- Chrome plated housing cap
- UL listed



Model No.	Mfg. No.	Gas Service	Max Inlet/Delivery Pressure (PSI)	Inlet Gauge	Outlet Gauge	Inlet Connection	Outlet Connection	Price /Each
331-4385	452X-80	Oxygen	3000/4-80	2", 4000 PSI	2", 100 PSI	CGA540	9/16"-18 RH (M)	199.00
331-4380	452X-175	Oxygen	3000/5-175	2", 4000 PSI	2", 300 PSI	CGA540	9/16"-18 RH (M)	189.00
331-4395	452Y-15	Acetylene	400/2-15	2", 400 PSI	2", 30 PSI, RL	CGA510	9/16"-18 LH (M)	199.00
TTT120	452C-175	Carbon Dioxide	3000/5-175	2", 4000 PSI	2", 300 PSI	CGA320	5/8"-18 RH (F)	199.00
331-4285	452C-300	Carbon Dioxide	3000/20-300	2", 4000 PSI	2", 400 PSI	CGA320	5/8"-18 RH (F)	319.00
TTT118	452IN-80	Inert Gases*	3000/4-80	2", 4000 PSI	2", 100 PSI	CGA580	5/8"-18 RH (F)	199.00
331-4340	452IN-300	Inert Gases*	3000/20-300	2", 4000 PSI	2", 400 PSI	CGA580	5/8"-18 RH (F)	279.00
804-1975	452IN-450	Inert Gases*	3000/30-450	2", 4000 PSI	2", 600 PSI	CGA580	5/8"-18 RH (F)	299.00

*Argon, nitrogen, helium

