

METAL WORKING FLUIDS & EQUIPMENT



LPS 3® PREMIER RUST INHIBITOR

- Protects up to two years
- Stops rust and corrosion
- Provides non-sling lubrication
- Non-flammable propellant
- Self-healing, waxy film
- Provides anti-seize coating
- Safe to use on rubber, fabric, plastics and paints
- Meets or exceeds these specs: Boeing BMS-3 23F Type II, MIL-C-0083933A, para.3.2-3.16, MIL-C-16173D Grade 2 Class I, DMS 2150, Airbus TN A. 007.10138 Type I Grade 2
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AA808	C00316	11 oz.	25.80
AB559	C00322	20-oz. Trigger	32.10
AB558	C03128	1 gal.	119.00
AB556	C00305	5 gal.	489.00
AB557	C00355	55 gal.	4239.00

COLD GALVANISED CORROSION INHIBITOR

- 95% zinc-rich galvanised coating
- Commonly used as a flash rust preventative on welded areas
- Works like a hot-dip on ferrous metals indoors and out
- Three-year protection
- Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C)
- Flexible coating will not yellow, chalk, crack or peel
- Electrochemically protect bare metal
- Meets or exceeds these specs: MIL-P-46105 Weld Through Primer, Passes Preece Test for Hot-Dip Galvanizing



Model No.	Mfg. No.	Size	Price /Each
AA807	C00516	14-oz.	20.50
AB552	C05128	1 gal.	429.00

BRIGHT COAT COLD GALVANIZED CORROSION INHIBITOR

- Shiny zinc coating
- Prevents rust and corrosion on all metals
- Restores hot dip galvanizing
- Dries to touch in 15 to 30 minutes
- Repairs rusted, galvanized and welded surfaces
- Electrochemically protects bare metal
- Heat resistant, flexible coating
- Will not yellow, chalk, crack or peel



Model No.	Mfg. No.	Size	Price /Each
AB485	C05916	13 oz.	17.80

EVAPO-RUST™ RUST REMOVER

- Removes rust quickly without scrubbing
- Dipping process
- Non-toxic, non-corrosive, non-flammable
- VOC free
- Water-soluble, biodegradable, safe on skin
- Contains no acids, bases or solvents
- Will not harm unrusted metals



Model No.	Mfg. No.	Size	Price /Each
AD049	ER1	1 L	11.05
AD050	ER4	3.78 L	36.03
AD051	ER20	18.9 L	171.00
AD052	ER205	205 L	1523.00

EXTEND® RUST TREATMENT

- Goes on white and converts rust to a durable, black, metal-protective coating in 10 minutes
- Wirebrush parts and apply with brush or spray
- Surface rust must be present
- Use as a primer or finish coat
- Resists temperatures to 250°F intermittent, 200°F continuous
- Approved by the American Bureau of Shipping



AA633

LOCTITE

Model No.	Mfg. No.	Size	Price /Each
AA633	234981	1 qt. bottle	54.10
AA634	160802	1 gal. bottle	185.00
AC110	234984	5 gal. pail	834.00

WL740 ZINC-RICH GALVANIZING COMPOUND

- Fast-drying, high-solids, high performance, epoxy-based coating
- Provides maximum protection to steel exposed to severe corrosive environments
- Fuses zinc to the metal substrate to protect against corrosion; equal to or better than hot-dipped galvanizing
- 97%-pure zinc dust
- May be topcoated with conventional primers or finish coats
- For fences, gutters, bridges, structural steel, wrought iron, farm equipment; ideal as a maintenance spray for highways, food plants, power plants, refineries or damaged galvanized surfaces



Model No.	Mfg. No.	Size	Price /Each
AA029	SC0740000	14 oz.	13.20

BIO-RUST NEUTRAL PH RUST REMOVER

- Removes rust and other metallic particles
- VOC free, solvent free, non-flammable, pH neutral solution biodegradable
- Not controlled under WHMIS
- Non-corrosive rust remover
- High workload - can remove 1.5 kg (3.3 lbs.) of iron oxide per 20 L
- For use with iron and mild steel
- Deeply rusted parts may require longer soaking time
- After application of Bio-Rust, rinse parts in water to remove loosened contaminants
- After removing rust, dip part into fresh bath or Bio-Rust to provide short term corrosion protection
- It is recommended to degrease part before using Bio-Rust
- Bio-Rust is designed for immersion applications only
- Immerse parts in Bio-Rust at room temperature and let react for at least 30 minutes

WALTER
Surface Technologies



Model No.	Mfg. No.	Size		Price /Each
		Litres	Gallons	
AD441	53-G 247	20	5.2	286.00
AD442	53-G248	208	55	2059.00